

### TEMPORARY DOWNPIPE



Product Code	Pricing Unit	Colour	Size	Downpipe Diameter (maximum)	Pack Quantity	Pallet Quantity
PSD1	EACH	Clear	150mm x 165m	95mm	1	40
PSD2	EACH	Clear	300mm x 165m	190mm	1	40

#### Product Description:

Proguard Temporary Downpipe is manufactured from flexible polythene material to aid in the protection of stone facades, brick elevations and woodwork during the construction process. The temporary downpipe sleeve is the best way to protect masonry from staining during a construction project until a permanent downpipe fixture can be installed.

Proguard polythene downpipe comes in two widths of 150mm and 300mm to fit varying widths of downpipe. This product can be fixed with cable ties or jubilee clips. The maximum downpipe diameter for PSD1 is 95mm and for PSD2 is 190mm.

#### Benefits:

- Heavy duty polythene to withstand the harshest weather.
- 100% waterproof.
- Lay-flat tubing is easy to store and transport.
- 165m on a roll.
- Available in 150mm and 300mm widths.
- Can be cut with a knife or scissors.
- Clear in colour.

#### Limitations:

- Requires fixing with cable ties or jubilee clips.
- Non-flame retardant.
- Intended for temporary use until a permanent downpipe is installed.

#### Application:

Unroll the downpipe and cut to the length required with a knife or scissors. Secure one end to the gutter opening with a *Proguard Cable Tie* or jubilee clip. This product can be left in place for the duration of project.