

VISQUEEN FLAME RETARDANT POLYTHENE PROTECTION



Product Code	Pricing Unit	Colour	Dimensions	Thickness (Gauge)	Pack Quantity	Pallet Quantity
PTHOF1	Each	Orange	4m x 25m	1000	1	20

Product Description:

Visqueen Flame Retardant Polythene Protection is used for surface protection, temporary screening, asbestos wrapping and more.

Fire retardant sheeting can be also used in various other applications whilst buildings undergo refurbishment work or in new build construction projects whilst also providing protection from dust and the risks of electrical hazards.

Benefits:

- 100% waterproof
- 250 microns (1000 gauge) thick
- Cost effective temporary protection
- Can be used to create a temporary dust screen
- Flexible material – ideal for draping and hanging
- Centre folded rolls
- Easily cut with a knife
- Flame Retardant to LPS1207 - Certificate Number 521a/03
- Manufactured in the UK
- Reusable and Recyclable

Limitations:

- Product may become slippery when wet. Mop up any spills immediately or replace where necessary.
- It is recommended that the membrane is used above 5 degrees Celsius.
- Typical rolls weigh over 15kg and care should be taken when handling the product in line with current manual handling regulations.

Application:

Each roll is centre folded. Simply unroll and unfold to use. Tape down any loose ends with *Proguard Low-tack PVC Tape* or *Proguard Ultra-Low Tack Tape* on sensitive surfaces.