PROGUARD

CORREX FLAME RETARDANT PROTECTION BOARD



Product Code	Pricing Unit	Colour	Dimensions	Thickness	Pack Quantity	Pallet Quantity
PBTFD12	Each	Translucent	2m x 1m	2mm	25	550
PBTFD13	Each	Translucent	2m x 1m	2.6mm	20	400
PBTF12	Each	Translucent	2.4m x 1.2m	2mm	25	550
PBTF13	Each	Translucent	2.4m x 1.2m	2.6mm	20	400
PBTF14	Each	Translucent	2.4m x 1.2m	3.5mm	10	300
PBBF12	Each	Black	2.4m x 1.2m	2mm	25	550

Product Description:

Correx Flame Retardant Protection Board is manufactured from strong corrugated polypropylene to provide long lasting protection for windows, doors, stairs, walls, and floors. Lightweight and extremely strong, the plastic sheets are tear, puncture, and impact resistant. They can be cut, curved and creased to fit any surface offering complete surface protection for a variety of applications during refurbishment, building and construction projects.

Benefits:

- Provides efficient protection from knocks, scratches, and spills.
- Lightweight and flexible.
- Quick and easy to cut, crease and curved.
- Durable and reusable.
- 100% waterproof.
- Personalised logo and branding printing available.
- Flame retardant to LPS1207. Certificate number 227a
- Resistant to chemicals.
- 100% Recyclable.

Limitations:

- Product may become slippery when wet. Mop up any spills immediately or replace where necessary.
- Not suitable for protection against heavy traffic i.e. Scissor-lifts. We recommend our Proguard Bufferboard for this application.

Application:

Ensure surfaces onto which Correx Flame Retardant Protection Board is to be laid are free from loose rubble. Beginning from the corner of the room lay the sheets side by side using Proguard Cloth Tape when joining the boards. Use Proguard Low Tack PVC tape when adhering to sensitive surfaces such as marble and glass. To ensure a completely residue-free removal we recommend using Proguard Ultra Low Tack tape.

Performance Data:



2mm (250gsm), 2.6mm (350gsm), 3.5mm (600gsm) 3.2 – 3.5mm Copolymer polypropylene (C3H6)n(C2H4)m