

12 MONTH WINDOW PROTECTION FILM



Product Code	Pricing Unit	Colour	Dimensions	Thickness	Pack Quantity	Pallet Quantity
PFW112M	EACH	CLEAR	1180mm x 50m	180 micron	1	24

Product Description:

Proguard 12 Month Window Protection Film is specially formulated for temporary protection of glass surfaces on site from manufacture and installation through to site hand over. The heavy-duty film is able to withstand heavy abrasions, welding and grinding sparks and corrosion from concrete or mortar splashes. The film is able to protect glass surfaces through every stage of the construction process and is particularly suited to protecting surfaces with specialist surface treatments or where replacement would be difficult and costly. The film is an excellent option in areas where it is necessary to retain natural light as it is semi-transparent, allowing maximum light transfer.

Benefits:

- Protects from damage
- Reusable
- Semi-transparent
- Easy to apply and remove
- No adhesive residue
- Easily portable
- Reaction to Fire test classification – EN 13501-1: B, S1, D0

Limitations:

- Do not use for longer than 12 months
- Film may experience yellowing in prolonged periods of exposure to high UV levels.

Application:

Measure the window size you wish to protect, roll out the film and mark the size and shape on the release liner at the reverse of the film. Cut out the size and shape of film that you require to cover the glass. Peel back the release liner from one edge and apply to the top of the window. Peel the release liner downwards, smoothing the film out as you work downwards.

Performance Data:

Temperature Resistance	-30°C to +60°C
Solar ray transmittance	50%
Adhesive	Pressure Sensitive Acrylic
Adhesive Strength	1 N / 25 mm
UV resistance	Up to 12 months
Backing	PVC Film – UV Stable